

TECHNICAL SPECIFICATIONS

Specifications >>>

Functions	Description
Monitoring Units	Wired : Max. 64 units Wireless : Max. 16 units
Supported Device Model	BM3, BM5, (BM3 Lite, BM3 Plus), BM7
Network	Wired : LAN Wireless : W-LAN
View Mode	2, 4, 8, 16, and 32 Monitors View Mode
Patient Data Storage	According to storage amount
Alarm	Sound and Display
Communication Type	Bi-directional control
Reviewer	Alarm, Waveform, Graphic Trend, and Tabular Trend
Print and Report	4 kinds of Report Form : Alarm, Waveform, Graphic Trend, and Tabular Trend
Certificate	CE 0123
HIS/EMR connection	HL7 support
Supported Language	English, Italian, French, Spanish, German, Chinese, Russian, Polish, Czech, Turkish, Romanian, Portugues, Bulgarian, Korean

Hardware Configuration >>>

BMCentral System (Wired LAN)	
Description	EA
Software BMCentral CD	1
Lock Key Central Software (USB Memory)	1
Op Manual/EN/BMCentral	1
Desktop PC (with monitor)-Dell	1
ACC. PC Speaker (Central)	1
HUB 16Port 3COM 18p 3C16470 10/100M	1
Cable LAN 30m	8
Cable LAN 5m	1

BMCentral System (Wireless LAN)	
Description	EA
Software BMCentral CD	1
Lock Key Central Software (USB Memory)	1
Op Manual/EN/BMCentral	1
Desktop PC(with monitor)-Dell	1
ACC. PC Speaker (Central)	1
Wireless Access Point	1
Wireless Ethernet Converter	8
Cable BM5 W-LAN 5.0 DC	8
Bracket W-Lan Holder	8



North America (U.S.A.):Bionet America Inc.
Tel.:+1-714-734-1780
E-mail:sales@bionetUS.com
www.bionetUS.com

South Korea:Bionet Co., Ltd.
Tel.:+82-70-7585-6419 (Int'l)
+82-2-6300-6483 (Domestic)
E-mail:sales@ebionet.com (Int'l)
yunms@ebionet.com (Domestic)
www.ebionet.com

Latin America:Bionet Latin America Inc.
Tel.:+82-70-7585-6419 (Int'l)
E-mail:sales@ebionet.com
www.ebionet.com

Europe:MGB Endoskopische
Geräte GmbH Berlin (Germany)
Tel.:+49-30-6392-7000
E-mail:sales@mgb-berlin.de
www.mgb-berlin.de

201206 BionetBMCentral P12.0

Patient Monitoring Central System

BMCentral

- Monitoring up to **64** beds simultaneously using wired LAN
- Wireless LAN available for monitoring up to **16** beds
- Bi-directional Control
- Up to 14 languages support
- CE Approval
- HIS/EMR connection support by sending HL7 message



